Building Services, Room 201 City-County Building 300 West Ash · P.O. Box 736 Salina, Kansas 67402-0736



TELEPHONE · (785) 309-5715

FAX · (785) 309-5713

TDD · (785) 309-5747

WEBSITE · www.salina-ks.gov

Commercial Stairs - Rough Inspection

DRAFT

Address:		contractor:		Permit #	
The following checklist is not all-inclusive. Other code related requirements may be included in this inspection					
OK Yes No n/a	Verify that work conforms to approved plans.		OK Yes No n/a	Verify that height between landings does	
OK Yes No n/a	Verify minimum 36" stairway width serving occupant load less than 50, otherwise minimum 44". IBC sec 1009.1		OK Yes No n/a	Verify that landings at the top and bottom of the flight of stairs are minimum 48" in length. IBC sec 1009.4	
OK Yes No n/a	Verify minimum stair width of 48" between handrails for stairs serving area of rescue. ADAAG sec 4.3.11.3		OK Yes No n/a	Verify required headroom. IBC sec 1009.2	
OK Yes No n/a	Verify maximum 7" riser height and minimum 11" tread width measured from nose to nose. IBC sec 1009.3		OK Yes No n/a	Verify that risers are closed on stairs that must comply with ADA. ADAAG sec 4.9.2	
OK Yes No n/a	Verify maximum 3/8" differential in riser heights or tread widths. IBC sec 1009.3.1		OK Yes No n/a	Verify that provisions have handrail extensions on bot stairs. IBC sec 1009.11.5	
OK Yes No n/a	Verify that tread nosing overhangs do not exceed 1¼" and profile complies with code. IBC sec 1009.3.2		OK Yes No n/a	Verify that provisions have a continuous handrail on b stairs. IBC sec 100911.4	
OK Yes No n/a	Verify that treads are level. IBC sec 1009.5.1		OK Yes No n/a	Verify adequacy of stair fra	aming.
Notes:					
Date	Insp	pector			